FEATURES

- Includes fully modulating economizer. (See Form ECO-184 for Economizer Specs).
- CO2 controller standard on economizer. Space or duct mounted CO2 sensor provided as option:
 - CO2WM Wall Mount With LED
 - CO2DM Duct Mount
- · LEED economizer option.
- · Access for motor, blower, and blower drives.
- · Adjustable motor sheave.
- · Motor with automatic internal thermal protection.
- Modulating option includes fully programmable (factory set) variable frequency drive controlled by a differential pressure transducer designed to continuosly monitor space pressure.

DOWN DISCHARGE CENTRIFUGAL POWER EXHAUST **ECONOMIZER FOR YORK UNITS**

ZH/ZF/ZR 102-150: ZJ/XP 078-150


VOLTAGE	Exte	rnal Sta	tic (in. V	FLA	Нр	Wt	
	0.1	0.2	0.3	0.4	, .	p	
230V/3Ph	4,200 cfm	4,000 cfm	3,900 cfm	3,800 cfm	5.6	2	220 Lbs. (Includes Economizer)
460V/3Ph					2.8		


	ProVent P/N							
	CONSTANT VOLUME	MODULATING						
	PEDCPRDLCDB25CS 208/230V 3Ph Selectable Dry Bulb	PEDCPRDLCDB25MS 208/230V 3Ph Selectable Dry Bulb						
	PEDCPRDLCEN25CS 208/230V 3Ph Enthalpy	PEDCPRDLCEN25MS 208/230V 3Ph Enthalpy						
	PEDCPRDLCDB46CS 460V 3Ph Selectable Dry Bulb	PEDCPRDLCDB46MS 460V 3Ph Selectable Dry Bulb						
r)	PEDCPRDLCEN46CS 460V 3Ph Enthalpy	PEDCPRDLCEN46MS 460V 3Ph Enthalpy						


Note: For factory installed LEED economizer / power exhaust option, part number, FLOWECPRD3715, must be added.

PLEASE NOTE:

- 1. Return air duct, dampers, return air grills are specific for each unit.
- 2. For proper electrical wire sizing, Provent power exhaust full load amps need to be added to equation.










Only Ruskin Company Model CD-60 is AMCA Certified

LEED ECONOMIZER / POWER EXHAUST OPTION

- ProVent P/N: FLOWECPRD3715
- Outside air measurement for dilution utilizing thermal dispersion technology and ASHRAE 62.1 compliant.
 Provides LEED credit by supplying feedback on ventilition system performance ensuring that the ventilation system maintains design requirements.
- Factory installed onto economizer/power exhaust standard.
- · Provides analog outputs for BMS, visual or audible alert, and generates an alarm when conditions vary by 10% or more of set point.



ProVent

3847 WABASH DR. MIRA LOMA, CA 91725

PHONE (951) 685-1101 FAX (619) 872-9799

SUBMITED TO:	FORM NO:	PART NU	PART NUMBER:	
COMPANY:	PE-88	PEDCPRDLCS SERIES		
JOB NAME:				
EQUIPMENT:	DATE: 8/12/2016	REV:	DRAWN BY:	
NOTES:	8/12/2016	1	JG	